

**STANDARD ROTA-CONE VACUUM DRYER SPECS**

Model #	Over-all Capacity Cu. Ft.	Working Capacity Cu. Ft.	Jacketed Surface Sq. Ft.	Vacuum Line In.	Std. HP	App-rox. RPM	Dis-charge Valve Dia-meter	Dis-charge Clearance In.	Over-all Height In.	Over-all Length In.	Swing Diam. In.	App-rox. Ship Weight Lbs.
RCVD-9	0.2	0.13	1.53	0.75	0.25	13	N/A	18	34	41	16	210
RCVD-12	0.5	0.33	2.92	1	0.25	10	N/A	18	38	40	20	280
RCVD-18	1.7	1.1	6.7	1	0.25	8	6	18	46	54	28	500
RCVD-24	3.9	2.5	11.9	1	0.25	7	6	18	56	64	38	830
RCVD-30	7.7	5.0	18.7	1.5	0.25	7	6	18	64	73	46	1,300
RCVD-36	13.5	8.8	27.4	1.5	0.25	6	6	18	71	80	53	2,100
RCVD-39	16.9	11.0	31.6	1.5	0.5	6	6	18	75	89	57	2,500
RCVD-42	21	13.7	36.5	1.5	0.5	6	6	18	79	92	61	2,900
RCVD-48	32	21	48	2	0.75	5	6	3	73	110	70	3,700
RCVD-54	45	29	62	2	1	5	8	3	83	123	80	4,400
RCVD-60	62	40	77	2	1.5	4	8	3	91	130	88	5,300
RCVD-66	83	54	93	3	2	4	10	3	100	141	97	6,200
RCVD-72	108	70	111	3	3	4	10	3	107	151	104	6,900
RCVD-78	137	89	131	3	3	4	10	3	115	160	112	7,900
RCVD-84	172	112	151	3	5	4	12	3	124	174	121	9,100
RCVD-90	210	137	174	4	5	3	12	3	132	186	129	10,400
RCVD-96	255	166	199	4	7.5	3	12	3	139	198	136	11,900
RCVD-102	305	198	225	4	7.5	3	12	3	147	206	144	14,000
RCVD-108	365	237	253	4	10	3	12	3	155	226	152	16,300
RCVD-114	426	277	282	4	10	3	12	3	162	240	159	18,300
RCVD-120	500	325	313	6	15	3	12	3	172	240	169	20,200